

# 2S

## 喷砂胶管

### Sandblasting hose

**用途:** 用于金属表面作风压喷砂除锈、打麻工程施工中湿砂和干砂的输送。

**特性:** 1.胶管采用耐磨性能优良的特种橡胶制造，骨架层为化学纤维缠绕结构，工作压力有4倍安全系数。

2.胶管外观为水布纹，颜色黑色。

**参考标准:** HG/T2192《喷砂橡胶软管》标准



#### APPLICATIONS:

This section covers hose for metal surface pressure sand-blasting, and the transport of wet sand and dry sand in Scutching engineering.

#### FEATURE:

- This hose using excellent wear resistance with special rubber manufacturing, the skeleton layer composed by chemical fiber winding structure, tube light. The working safety factor up to four times.
- Cloth wrapped cover, and the color is black.

型号 TYPE	内径 I.D		外径 O.D	层数 s	最大 工作压力 W.P		最小 爆破压力 B.P		最大长度 Max Length mm	参考 重量 W.T kg/m
	in	mm	mm		Mpa	Psi	Mpa	Psi		
13-2S-0.8	½	13	26	2	0.8	116	3.2	464	40	0.40
16-2S-0.8	5/8	16	29	2	0.8	116	3.2	464	40	0.50
19-2S-0.8	¾	19	32	2	0.8	116	3.2	464	40	0.60
25-2S-0.8	1	25	38	2	0.8	116	3.2	464	40	0.81
32-2S-0.8	1-¼	32	48	2	0.8	116	3.2	464	40	1.10
38-2S-0.8	1-½	38	54	2	0.8	116	3.2	464	40	0.92
51-2S-0.8	2	51	67	2	0.8	116	3.2	464	40	1.75
13-2S-1.0	½	13	26	2	1.0	145	4.0	580	40	0.42
16-2S-1.0	5/8	16	29	2	1.0	145	4.0	580	40	0.52
19-2S-1.0	¾	19	32	2	1.0	145	4.0	580	40	0.62
25-2S-1.0	1	25	38	2	1.0	145	4.0	580	40	0.83
32-2S-1.0	1-¼	32	48	2	1.0	145	4.0	580	40	1.12
38-2S-1.0	1-½	38	54	2	1.0	145	4.0	580	40	0.94
51-2S-1.0	2	51	67	2	1.0	145	4.0	580	40	1.79

注：表中未列入的规格或工作压力等级，可按客户要求另行设计生产。