

产品系列-编织管

PRODUCT SERIES-BRAIDED HOSES



E-mail:sales@showinflex.com

Website: www.showinhydro.com

EN857-2SC / 钢丝编织液压橡胶软管

Wire Braided Hydraulic Hose

结构:

软管由一层耐油合成橡胶内胶层、两层钢丝增强层和一层耐油、耐天候的合成橡胶外胶层组成。

应用:

适用于液压流体和水性流体,工作温度范围-40°C~+100°C (-40°F ~ 212°F)。



CONSTRUCTION:

This hose shall consist of an oil and water resistant synthetic rubber lining,two layers of tensile steel wire and an oil and weather resistant synthetic rubber cover.

APPLICATIONS:

Suitable for use with hydraulic fluids or water-based fluids within a temperature range of-40°C ~ +100°C(-40°F ~ 212°F).

型号 TYPE	公制 规格 SIZE	英制 规格 SIZE	SAE 短划线 规格	内径 I.D		增强层直径 W.D		外径 O.D	最大 工作压力 W.P		试验压力 P.P		最小 爆破压力 B.P		最小 弯曲半径 Min B.R		参考 重量 W.T
				最小	最大	最小	最大		MPa	Psi	MPa	Psi	MPa	Psi	inch	mm	
				Min	Max	Min	Max		Max								
2SC-06	6.3	1/4	-4	6.1	6.9	10.6	11.7	14.2	40.0	5800	80.0	11600	160.0	23200	2.95	75	0.27
2SC-08	8	5/16	-5	7.7	8.5	12.1	13.3	16.0	35.0	5075	70.0	10150	140.0	20300	3.35	85	0.33
2SC-10	10	3/8	-6	9.3	10.1	14.4	15.6	18.3	33.0	4785	66.0	9570	132.0	19140	3.54	90	0.41
2SC-13	12.5	1/2	-8	12.3	13.5	17.5	19.1	21.5	27.5	3990	55.0	7975	110.0	15950	5.12	130	0.52
2SC-16	16	5/8	-10	15.5	16.7	20.5	22.3	24.7	25.0	3625	50.0	7250	100.0	14500	6.69	170	0.63
2SC-19	19	3/4	-12	18.6	19.8	24.6	26.4	28.6	21.5	3120	43.0	6235	86.0	12470	7.87	200	0.81
2SC-25	25	1	-16	25.0	26.4	32.5	34.3	36.6	16.5	2390	33.0	4785	66.0	9570	9.84	250	1.13