

产品系列-编织管

PRODUCT SERIES-BRAIDED HOSES



E-mail:sales@showinflex.com

Website: www.showinhydro.com

EN853-2SN / 钢丝编织液压橡胶软管

Wire Braided Hydraulic Hose

结构:

软管由一层耐油合成橡胶内胶层、二层钢丝编织层和一层耐油、耐天候的合成橡胶外胶层组成。

应用:

适用于使用石油基液压油, 温度范围为- 40°C~ +100°C (-40°F ~ 212°F)的软管。



CONSTRUCTION:

This hose shall consist of an inner tube of oil resistant synthetic rubber, two braids of steel wire reinforcement, and an oil and weather resistant synthetic rubber cover.

APPLICATIONS:

This section covers hose for use with petroleum base hydraulic fluids within a temperature range of-40°C~+100°C(-40°F~ 212°F).

型号 TYPE	公制 规格 SIZE	英制 规格 SIZE	SAE 短划线 规格	 内径 I.D		 增强层直径 W.D		 外径 O.D		 最大 工作压力 W.P		 试验压力 P.P		 最小 爆破压力 B.P		 最小 弯曲半径 Min B.R		 参考 重量 W.T
				最小	最大	最小	最大	最小	最大									
	mm	inch	1/16	Min	Max	Min	Max	Min	Max	MPa	Psi	MPa	Psi	MPa	Psi	inch	mm	kg/m
2SN-05	5	3/16	-3	4.8	5.2	11.0	11.5	12.8	13.3	41.5	6020	83.0	12040	165.0	23930	3.54	90	0.32
2SN-06	6.3	1/4	-4	6.2	6.6	12.6	13.2	14.6	15.2	40.0	5800	80.0	11600	160.0	23200	3.94	100	0.35
2SN-08	8	5/16	-5	8.0	8.4	13.9	14.5	15.8	16.4	35.0	5080	70.0	10150	140.0	20300	4.53	115	0.45
2SN-10	10	3/8	-6	9.7	10.1	16.2	16.8	18.3	18.9	33.0	4790	66.0	9570	132.0	19140	5.12	130	0.54
2SN-13	12.5	1/2	-8	12.9	13.4	19.3	19.9	21.4	22.0	27.5	3990	55.0	7980	110.0	15950	7.09	180	0.68
2SN-16	16	5/8	-10	16.0	16.5	22.5	23.1	24.5	25.1	25.0	3625	50.0	7250	100.0	14500	7.87	200	0.80
2SN-19	19	3/4	-12	19.0	19.5	26.4	27.0	28.4	29.0	21.5	3120	43.0	6235	86.0	12330	9.45	240	0.94
2SN-25	25	1	-16	25.2	25.8	34.4	35.0	36.9	37.5	16.5	2400	33.0	4710	66.0	9430	11.81	300	1.38
2SN-32	31.5	1-1/4	-20	31.5	32.0	42.7	43.3	45.6	46.4	12.5	1810	25.0	3630	50.0	7250	16.54	420	2.15
2SN-38	38	1-1/2	-24	38.0	38.5	49.9	50.5	52.7	53.5	9.0	1300	18.0	2610	36.0	5220	19.69	500	2.65
2SN-51	51	2	-32	51.0	51.5	62.7	63.3	65.7	66.5	8.0	1160	16.0	2320	32.0	4640	24.80	630	2.75