

产品系列-缠绕管

PRODUCT SERIES-SPIRAL HOSES



E-mail:sales@showinflex.com

Website: www.showinhydro.com

EN856-4SP / 钢丝缠绕液压橡胶软管


Wire Spiral Hydraulic Hose

结构:

软管由一层耐油合成橡胶内胶层、四层交替方向的钢丝缠绕层和一层耐油、耐天候的合成橡胶外胶层组成。

应用:

适用于使用石油基液压油, 温度范围为-40°C~+100°C (-40°F~212°F)的软管。



CONSTRUCTION:

This hose shall consist of an inner tube of oil resistant synthetic rubber, four spiral plies of steel wire wrapped in alternating directions, and an oil and weather resistant synthetic rubber cover.

APPLICATIONS:

This section covers hose for use with petroleum base hydraulic fluids within a temperature range of -40°C~+100°C(-40°F~212°F).

型号 TYPE	公制 规格 SIZE	英制 规格 SIZE	SAE 短划线 规格	内径 I.D		增强层直径 W.D		外径 O.D		最大 工作压力 W.P		试验压力 P.P		最小 爆破压力 B.P		最小 弯曲半径 Min B.R		参考 重量 W.T
				最小	最大	最小	最大	最小	最大	MPa	Psi	MPa	Psi	MPa	Psi	inch	mm	
				Min	Max	Min	Max	Min	Max	MPa	Psi	MPa	Psi	MPa	Psi	inch	mm	
4SP-06	6.3	1/4	-4	6.2	6.6	14.1	14.7	17.1	17.7	45.0	6530	90.0	13050	180.0	26100	5.91	150	0.64
4SP-10	10	3/8	-6	9.7	10.1	17.2	17.8	20.6	21.2	44.5	6450	89.0	12900	178.0	25810	7.09	180	0.82
4SP-13	12.5	1/2	-8	12.9	13.4	20.4	21.0	23.8	24.4	41.5	6000	83.0	12040	166.0	24070	9.06	230	0.87
4SP-16	16	5/8	-10	16.0	16.5	23.7	24.3	27.4	28.0	35.0	5080	70.0	10150	140.0	20300	9.84	250	1.19
4SP-19	19	3/4	-12	19.0	19.5	27.6	28.2	31.4	32.0	35.0	5080	70.0	10150	140.0	20300	11.81	300	1.49
4SP-25	25	1	-16	25.2	25.7	34.6	35.4	38.5	39.1	28.0	4060	56.0	8120	112.0	16240	13.39	340	2.02
4SP-32	31.5	1-1/4	-20	31.5	32.0	45.0	45.8	49.2	50.0	21.0	3050	42.0	6090	84.0	12180	18.11	460	3.05
4SP-38	38	1-1/2	-24	38.0	38.5	51.4	52.2	55.6	56.4	18.5	2680	37.0	5360	74.0	10730	22.05	560	3.51
4SP-51	51	2	-32	51.0	51.5	64.3	65.1	68.2	69.0	16.5	2390	33.0	4790	66.6	9570	25.98	660	4.35