

产品系列-缠绕管

PRODUCT SERIES-SPIRAL HOSES



E-mail:sales@showinflex.com
Website: www.showinhydro.com

SAE100R15 / 钢丝缠绕液压橡胶软管

Heavy Duty, High Impulse, Multiple Spiral Steel Wire Reinforced, Rubber Covered Hydraulic Hose

结构:

软管由一层耐油合成橡胶内胶层、多层交替方向缠绕的钢丝层和一层耐油、耐天候的合成橡胶外胶层组成。

应用:

适用于液压流体和水性流体, 工作温度范围-40°C~+121°C (-40°F~250°F)。



CONSTRUCTION:

This hose shall consist of an inner tube of oil resistant synthetic rubber multiple spiral plies of heavy steel wire wrapped in alternating directions, and an oil and weather resistant synthetic rubber cover.

APPLICATIONS:

This hose for use with petroleum-based hydraulic fluids within a temperature range of -40°C~+121°C (-40°F~250°F).

型号 TYPE	公制 规格 SIZE	英制 规格 SIZE	SAE 短划线 规格	内径 I.D		增强层直径 W.D	外径 O.D	最大 工作压力 W.P		试验压力 P.P		最小 爆破压力 B.P		最小 弯曲半径 Min B.R		参考 重量 W.T
				最小	最大	最大		MPa	Psi	MPa	Psi	MPa	Psi	inch	mm	
				mm	inch	1/16		Min	Max	Max	Max	Max	Max	Max	Max	
R15-10	10	3/8	-6	9.3	10.1	20.3	23.3	42.0	6090	84.0	12180	168.0	24360	5.91	150	0.75
R15-13	12.5	1/2	-8	12.3	13.5	24.0	26.8	42.0	6090	84.0	12180	168.0	24360	7.87	200	0.90
R15-19	19	3/4	-12	18.6	19.8	32.9	36.1	42.0	6090	84.0	12180	168.0	24360	10.43	265	1.40
R15-25	25	1	-16	25.0	26.4	38.9	42.9	42.0	6090	84.0	12180	168.0	24360	12.99	330	2.10
R15-32	31.5	1-1/4	-20	31.5	32.0	48.4	51.5	42.0	6090	84.0	12180	168.0	24360	17.52	445	3.90
R15-38	38	1-1/2	-24	37.7	39.3	56.3	59.6	42.0	6090	84.0	12180	168.0	24360	20.87	530	4.65