

产品系列-编织管

PRODUCT SERIES-BRAIDED HOSES



E-mail:sales@showinflex.com

Website: www.showinhydro.com

SAE100R3 / 双层(非金属)橡胶液压软管


Double Fiber Braid(Nonmetallic),Rubber Covered Hydraulic Hose

结构:

软管由一层耐油合成橡胶内胶层、二层纤维编织层和一层耐油、耐天候的合成橡胶外胶层组成。

应用:

适用于输送液压流体如醇、液压油、燃油、润滑油、乳化液、烃等。工作温度为-40°C~+100°C(-40°F~212°F)。



CONSTRUCTION:

This hose shall consist of an inner tube of oil resistant synthetic rubber, two braids of suitable fiber, and an oil and weather resistant synthetic rubber cover.

APPLICATIONS:

Suitable for use with hydraulic fluids such as glycol, mineral oils, fluids, lubrication, emulsion, hydrocarbons etc. working temperature range from -40°C ~ +100°C(-40°F ~212°F).

型号 TYPE	公制 规格 SIZE	英制 规格 SIZE	SAE 短划线 规格	内径 I.D		外径 O.D		最大 工作压力 W.P		试验压力 P.P		最小 爆破压力 B.P		最小 弯曲半径 Min B.R		参考 重量 W.T
				最小	最大	最小	最大	MPa	Psi	MPa	Psi	MPa	Psi	inch	mm	
				mm	inch	1/16	Min	Max	Min	Max	MPa	Psi	MPa	Psi	MPa	
R3-05	5	3/16	-3	4.5	5.4	11.9	13.5	10.5	1523	21	3046	42	6092	2.95	75	0.16
R3-06	6.3	1/4	-4	6.1	7.0	13.5	15.1	8.7	1262	17.5	2538	35	5076	2.95	75	0.18
R3-08	8	5/16	-5	7.6	8.5	16.7	18.3	8.4	1218	16.8	2437	33.5	4859	3.94	100	0.27
R3-10	10	3/8	-6	9.4	10.1	18.3	19.8	7.8	1131	15.7	2277	31.5	4569	3.94	100	0.31
R3-13	12.5	1/2	-8	12.4	13.5	23.0	24.6	7	1015	14	2031	28	4061	4.92	125	0.45
R3-16	16	5/8	-10	15.6	16.7	26.2	27.8	6.1	885	12.2	1769	24.5	3553	5.51	140	0.53
R3-19	19	3/4	-12	18.7	19.8	31.0	32.5	5.2	754	10.5	1523	21	3046	5.91	150	0.72
R3-25	25	1	-16	25.1	26.2	36.9	39.3	3.9	566	7.8	1131	15.7	2277	8.07	205	0.90
R3-32	32	1-1/4	-20	31.4	32.9	42.9	46.0	2.6	377	5.2	754	10.5	1523	9.84	250	1.07